



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s): Akira YOKOYAMA

Group Art Unit: 2873

Serial No.:

09/988,259

Examiner:

Huy K. MAI

Filed:

November 19, 2001

For:

DRIVE TRANSMISSION DEVICE AND OPTICAL APPARATUS USING THE

SAME

AMENDMENT UNDER 37 C.F.R. § 1.114

Mail Stop RCE Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

This amendment accompanies a Request for Continued Examination (RCE) and is being filed pursuant to 37 C.F.R. §1.114.

Amendments to the Claims are reflected in the listing of claims which begins on page 2 of this paper.

Remarks/Arguments begin on page 16 of this paper.

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

 (currently amended) A drive transmission device for transmitting drive of an actuator to a driven member, the drive transmission device comprising:

an input member which is driven by the actuator[[;]], the input member having an input contact surface; and

an output member which transmits drive of the input member and drives the driven member[[;]], the output member having an output contact surface;

wherein the drive transmission device is switchable between a first state in which the drive of the input member is transmitted to the output member and a second state in which the drive of the input member is not transmitted to the output member,

and the input member contact surface and the output member contact surface are in contact with each other when the drive transmission device is in the first state and in the second state[[.]], and

a contact pressure between the input contact surface and the output contact surface in the first state is larger than a contact pressure therebetween in the second state.

2. (Previously presented) The drive transmission device according to Claim 1, wherein the drive transmission device is an electromagnetic clutch for generating an electromagnetic force by supplying electricity, the electromagnetic clutch bringing the input member and the output member into contact with each other with contact pressure by the electromagnetic force corresponding to an electricity supply value in the first state.

- 3. (Previously presented) The drive transmission device according to Claim 1, wherein the drive transmission device is an electromagnetic clutch for generating an electromagnetic force by supplying electricity, the electromagnetic clutch bringing the input member and the output member into contact with each other with contact pressure by the electromagnetic force corresponding to an electricity supply value in the second state.
- (Original) The drive transmission device according to Claim 1, wherein the actuator is a motor.
- 5. (canceled).
- (currently amended) The drive transmission device according to Claim 51, wherein a
 lubricant to give slidability is applied onto the input contact surface and onto the
 output contact surface.
- 7. (Original) The drive transmission device according to Claim 6, wherein the lubricant is grease.
- 8. (Original) The drive transmission device according to Claim 51, wherein at least one of either the input contact surface or the output contact surface is treated with electrolytic plating or electroless plating to give slidability.

- (Original) The drive transmission device according to Claim 8, wherein a lubricant to give slidability is applied onto the contact surface.
- (Original) The drive transmission device according to Claim 9, wherein the lubricant is grease.
- 11. (currently amended) The drive transmission device according to Claim 51, wherein an intermediate member to give slidability is provided between the input contact surface and the output contact surface.
- 12. (Original) The drive transmission device according to Claim 11, wherein the intermediate member is made of at least one of either Teflon or polyethylene.
- 13. (Currently Amended) An optical apparatus A zoom lens comprising
 an optical member which is driven by a manual-drive member;
 an actuator; and
 - a drive transmission device for transmitting drive of the actuator to the optical member,

wherein the drive transmission device comprises:

an input member driven by the actuator[[;]], the input member having a an

input contact surface; and

an output member which transmits drive of the input member[[;]], the output member having an output contact surface;

wherein the drive transmission device is switchable between a first state in which the drive of the input member is transmitted to the output member and a second state in which the drive of the input member is not transmitted to the output member,

and the input membercontact surface and the output membercontact surface are in contact with each other when the drive transmission device is in the first state and in the second state[[.]], and

a contact pressure between the input contact surface and the output contact surface in the first state is larger than a contact pressure therebetween in the second state.

- 14. (currently amended) The zoom lens optical apparatus according to Claim 13, wherein the drive transmission device is an electromagnetic clutch for generating an electromagnetic force by supplying electricity, the electromagnetic clutch bringing the input member and the output member into contact with each other with contact pressure by the electromagnetic force corresponding to an electricity supplying value in the first state.
- 15. (currently amended) The <u>zoom lens optical apparatus</u>-according to Claim 13, wherein the optical member is a zoom lens unit.
- 16. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 13, wherein the optical member is a focus lens unit.
- (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 13, wherein the optical member is a stop unit.

- (currently amended) The <u>zoom lens optical apparatus</u>-according to Claim 13, wherein the actuator is a motor.
- 19. (canceled).
- 20. (currently amended) The zoom lens optical apparatus according to Claim 1913, wherein a lubricant to give slidability is applied onto the input contact surface and onto the output contact surface.
- (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 20, wherein the lubricant is grease.
- 22. (currently amended) The zoom lens optical apparatus according to Claim 1913, wherein at least one of either the input contact surface or the output contact surface is treated with electrolytic plating or electroless plating to give slidability.
- 23. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 22, wherein a lubricant to give slidability is applied onto the contact surface.
- 24. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 23, wherein the lubricant is grease.

- 25. (currently amended) The <u>zoom lens optical apparatus</u>-according to Claim <u>1913</u>, wherein an intermediate member to give slidability is provided between the input contact surface and the output contact surface.
- 26. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 25, wherein the intermediate member is made of at least one of either Teflon or polyethylene.
- 27. (currently amended) The zoom lens optical apparatus-according to Claim 14, further comprising a controller for controlling an electricity supplying value for the electromagnetic clutch so as to vary contact pressure between the input member and the output member.
- 28. (currently amended) A zoom lens An optical apparatus comprising:

an optical member which is driven by a manual-drive member;

an actuator; and

a drive transmission device for transmitting drive of the actuator to the optical member,

wherein the drive transmission device comprises:

an input member driven by the actuator[[;]], the input member having an input contact surface; and

an output member which transmits drive of the input member[[;]], the output member having an output contact surface;

a command unit which commands the optical member to be electrically driven, the command unit outputting command information in accordance with operation of a command operating member to the actuator; and

a controller which controls the drive transmission device in accordance with the command information from the command unit;

wherein the drive transmission device is switchable between a first state in which the drive of the input member is transmitted to the output member and a second state in which the drive of the input member is not transmitted to the output member,

and the input member contact surface and the output contact surface member are in contact with each other when the drive transmission device is in the first state and in the second state[[.]], and

a contact pressure between the input contact surface and the output contact surface in the first state is larger than a contact pressure therebetween in the second state.

- 29. (currently amended) The zoom lens optical apparatus according to Claim 28, wherein the controller brings the drive transmission device into the first state when there is no command information from the command unit or when command information does not exceed a predetermined range, whereas the controller brings the drive transmission device into the second state when there is command information from the command unit or when command information exceeds the predetermined range.
- 30. (currently amended) The zoom lens optical apparatus according to Claim 28, wherein the drive transmission device is an electromagnetic clutch for generating an electromagnetic force by supplying electricity, the electromagnetic clutch bringing the input member and the output member into contact with each other with contact pressure by the electromagnetic force corresponding to an electricity supply value.

and the controller controls an electricity supply value for the clutch in accordance with command information from the command unit.

- 31. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 30, wherein the controller brings the electromagnetic clutch into a state of non-electricity supply when there is no command information from the command unit or when command information does not exceed a predetermined range, whereas, when there is command information from the command unit or when command information exceeds the predetermined range, the controller brings the electromagnetic clutch into a state of electricity supply and sets an electricity supply value for the electromagnetic clutch at an electricity supply value according to the command information.
- 32. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 28, wherein the command unit has an operating member operated for commanding the optical member to be electrically driven, and the actuator that outputs command information in accordance with operation of the operating member works at a speed corresponding to the command information that varies in accordance with an operational amount of the operating member.
- (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 28, wherein the optical member is a zoom lens unit.
- 34. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 28, wherein the optical member is a focus lens unit.

4

- 35. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 28, wherein the optical member is a stop unit.
- 36. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 28, wherein the command information is a zoom driving signal.
- (currently amended) The zoom lens optical apparatus according to Claim 28, wherein the command information is a focus driving signal.
- 38. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 28, wherein the command information is a stop driving signal.
- (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 28, wherein the actuator is a motor.
- 40. (canceled).
- 41. (currently amended) The <u>zoom lens</u> optical apparatus according to Claim 4028, wherein a lubricant to give slidability is applied onto the input contact surface and onto the output contact surface.
- 42. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 41, wherein the lubricant is grease.

- 43. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 4028, wherein at least one of either the input contact surface or the output contact surface is treated with electrolytic plating or electroless plating to give slidability.
- 44. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 43, wherein a lubricant to give slidability is applied onto the contact surface.
- 45. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 44, wherein the lubricant is grease.
- 46. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 4028, wherein an intermediate member to give slidability is provided between the input contact surface and the output contact surface.
- 47. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 46, wherein the intermediate member is made of at least one of either Teflon or polyethylene.
- 48. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 30, wherein the controller controls an electricity, supply value for the electromagnetic clutch so as to satisfy the relation:

Tk'<Td'<Tm

where Tm is a maximum driving torque occurring at the input member driven by the actuator; Tk' is driving-torque needed to drive the output member that drives the optical member through the manual-drive member, and Td' is engagement torque corresponding to contact pressure between the input member and the output member.

49. (currently amended) The <u>zoom lensdrive transmission device</u> according to Claim 48, wherein the controller controls an electricity value for the electromagnetic clutch so as to satisfy the relation:

Td'<Tsy'

where Tsy' is manual driving torque transmitted from the manual-drive member to the output member through manual operation when the optical member is electrically driven by the actuator, thereby allowing the optical member to be manually driven while being electrically driven.

50. (currently amended) The zoom lensoptical apparatus according to Claim 30, wherein, when the optical member is not electrically but manually driven, the controller controls an electricity supply value for the electromagnetic clutch so as to satisfy the relation:

 $0 \le Td'' \le Tk'$

where Tk' is driving torque needed to drive the output member that drives the optical member through the manual-drive member while being electrically driven, and Td" is engagement torque corresponding to contact pressure between the input member and the output member when manually driven.

51. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 50, wherein the controller controls an electricity supply value for the electromagnetic clutch so as to satisfy the relation:

0<Td"<Tk'.

- 52. (currently amended) The <u>zoom lens optical apparatus</u> according to Claim 30, further comprising an adjusting member operated to vary engagement torque of the electromagnetic clutch, wherein the controller controls an electricity supply value for the electromagnetic clutch in accordance with operation of the adjusting member and varies the engagement torque when the optical member is manually operated.
- 53. (currently amended) The zoom lens optical apparatus according to Claim 30, wherein the controller controls an electricity supply value for the electromagnetic clutch in accordance with operation of the manual-drive member by a user.
- 54. (currently amended) A camera system An optical apparatus-comprising:

 an optical member which is driven by a manual-drive member;

 a zoom lens an optical unit which supports has the optical member;

 a camera systeman imaging unit to which the optical unit zoom lens is

 detachably mounted, the imaging unit camera having an image pickup device which

 picks up an object image from the zoom lensoptical unit;

an actuator; and

a drive transmission device for transmitting drive of the actuator to the optical member;

wherein the drive transmission device comprises:

an input member driven by the actuator[[;]], the input member having an input contact surface;

an output member which transmits drive of the input member[[;]], the output member having an output contact surface;

a command unit which commands the optical member to be electrically driven, the command unit outputting command information in accordance with operation of a command operating member to the actuator; and

a controller which controls the drive transmission device in accordance with the, command information from the command unit;

wherein the drive transmission device is switchable between a first state in which the drive of the input member is transmitted to the output member and a second state in which the drive of the input member is not transmitted to the output member,

and the input member contact surface and the output member contact surface are in contact with each other when the drive transmission device is in the first state and in the second state[[.]], and

a contact pressure between the input contact surface and the output contact surface in the first state is larger than a contact pressure therebetween in the second state.

55. (currently amended) An optical-apparatus driving unit mounted or connected to a body of an optical apparatus including an optical member a zoom lens and a manual-operating member which manually drives the optical-member zoom lens, the optical-apparatus driving unit comprising:

an actuator; and

a drive transmission device for transmitting drive of the actuator to the optical member,

wherein the drive transmission device comprises:

an input member driven by the actuator[[;]] the input member having an input contact surface

an output member which transmits drive of the input member[[;]], the output member having an output contact surface;

a command unit which commands the optical member to be electrically driven, the command unit outputting command information in accordance with operation of a command operating member to the actuator; and

a controller which controls the drive transmission device in accordance with the command information from the command unit;

wherein the drive transmission device is switchable between a first state in which the drive of the input member is transmitted to the output member and a second state in which the drive of the input member is not transmitted to the output member,

and the input membercontact surface and the output membercontact surface are [[In]] in contact with each other when the drive transmission device is in the first state and in the second state[[.]], and

a contact pressure between the input contact surface and the output contact

surface in the first state is larger than a contact pressure therebetween in the second

state.

REMARKS

Applicant respectfully requests the entry and consideration of this preliminary amendment filed in connection with a Request for Continued Examination under 37 C.F.R. §1.114.

CONCLUSION

In the event that the Examiner believes that a telephone conference would help to expedite the prosecution of this case, the Examiner is cordially invited to call the undersigned at the number provided below.

AUTHORIZATION

The Commissioner is hereby authorized to charge any additional fees which may be required for consideration of this Amendment to Deposit Account No. <u>13-4500</u>, Order No. <u>1232-4785</u>. A DUPLICATE OF THIS DOCUMENT IS ATTACHED.

Respectfully submitted, MORGAN & FINNEGAN, L.L.P.

Dated: July 9, 2004

By:

Joseph D. Eng Jr.

Registration No. <u>54,084</u>

(212) 758-4800 Telephone (212) 751-6849 Facsimile

Correspondence Address:

MORGAN & FINNEGAN, L.L.P. 345 Park Avenue New York, NY 10154-0053

REMARKS

Applicant respectfully requests the entry and consideration of this preliminary amendment filed in connection with a Request for Continued Examination under 37 C.F.R. §1.114.

CONCLUSION

In the event that the Examiner believes that a telephone conference would help to expedite the prosecution of this case, the Examiner is cordially invited to call the undersigned at the number provided below.

AUTHORIZATION

The Commissioner is hereby authorized to charge any additional fees which may be required for consideration of this Amendment to Deposit Account No. 13-4500, Order No. 1232-4785. A DUPLICATE OF THIS DOCUMENT IS ATTACHED.

Respectfully submitted,

MORGAN & FINNEGAN, L.L.P.

Dated: July 9, 2004 By:


Joseph D. Eng Jr.

Registration No. <u>54,084</u> (212) 758-4800 Telephone

(212) 751-6849 Facsimile

Correspondence Address:

MORGAN & FINNEGAN, L.L.P. 345 Park Avenue New York, NY 10154-0053





IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Akira YOKOYAMA

Group Art Unit:

2873

Serial No .:

09/988,259

Examiner:

Huy K. Mai

Filed:

November 19, 2001

For:

DRIVE TRANSMISSION DEVICE AND OPTICAL APPARATUS USING THE SAME

EXPRESS MAIL CERTIFICATE

Mail Stop RCE Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Express Mail Label No.: EV 357 803 569US

Date of Deposit: July 9, 2004

I hereby certify that the following attached paper(s) and/or fee

- 1. Request for Continued Examination;
- 2. Amendment under 37 CFR 1.114;
- 3. Information Disclosure Statement;
- 4. Form PTO 1449;
- 5. One cited reference;
- 6. Change of Correspondence Address;
- 7. Check of \$770.00 for RCE Fee;
- 8. Return postcard

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. §1.10 on the date indicated above and is addressed to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Susan Shen-Frattura

(Typed or printed name of person mailing papers(s) and/or

fee) [/

(Signature of person mailing paper(s) and/or fee)

Correspondence Address:

MORGAN & FINNEGAN, L.L.P. 345 Park Avenue
New York, NY 10154-0053
(212) 758-4800 Telephone
(212) 751-6849 Facsimile



↑CUSTOMER NUMBER↑

FOR CONTINUED EXAMINATION (RCE) TRANSMITTAL

Subsection (b) of 35 U.S.C. §132, effective on May 29, 2000, provides for continued examination of an utility or plant application filed on or after June 8, 1995.

	15.83
Application No.	09/988,259
Filing Date	November 19, 2001
First Named Inventor	Akira YOKOYAMA
Group Art Unit	2873 FEGH CENTER CONTROL
Examiner Name	Huy Kim MAI
Atty Docket No.	1232-4785

			****	od on or untor sume o, 1995.	Ditarinities 14as	1110				
See The American Inventors Protection Act of 1999 (AIPA)					Atty Docket N	No.	1232-4785			
Thi	s is a	Requ	est for Co	ontinued Examination (RCE) under 37 C.F.R.			lentified appli	cation.		
···		<u>NOTE:</u> a continu the AIPA	37 C.F.R. §1 ued prosecut . See Chang	1.114 is effective on May 29, 2000. If the above-identified applition application (CPA) under 37 C.F.R. §1.53(d) (PTO/SB/29) in ges to Application Examination and Provisional Application Pra 1, 2000), which established RCE practice.	cation was filed pri stead of a RCE to i	ior to May . be eligible	29, 2000, applican for the patent term	t may wish to consider filing adjustment provisions of		
1.	S	uhmiss	sion unde	er 37 C.F.R. §1.114						
	a.									
	٠									
			i. Consider the amendment(s)/reply under 37 C.F.R. §1.116 previously filed on (Any unentered amendment(s) referred to above will be entered).							
	ii. Consider the arguments in the Appeal Brief or Reply Brief previously filed on									
			iii. 🗍							
b. Enclosed										
			i. 🖂	Amendment/Reply						
•			ii. 🔲	Affidavit(s)/Declaration(s)	97444555					
			iii. 🛛	☐ Information Disclosure Statement (IDS)		07/14/2004 BDIRETA1 00000117 09988259				
			iv. Oth	er: Form PTO 1449 and 1 reference	01 FC:1001		77	70.00 OP		
2.	М	iscella	naane							
۷.		ISCEIIA		باله و من و و و در م د			07 077 01	100() 6		
	a.		Suspension of action on the above-identified application is requested under 37 C.F.R. §1.103(c) for a period of months. (Period of suspension shall not exceed 3 months; Fee under 37 C.F.R. §1.17(i) required)							
	_			_ months. (1 error of suspension shall not exce	teu 5 monuis,	ree une	ici 5/ C.r.R.	§1.17(1) required)		
	b.	Othe		•						
3.	L	Fee	es	The RCE fee under C.F.R. §1.17(e) is required by 37 C.	F.R. §1.114 when	n the RCE	E is filed			
	a.			ector is hereby authorized to charge the follow t No. 13-4500,	ing fees, or cr	redit any	overpayment	ts, to Deposit		
			i. 🗌	RCE fee required under 37 C.F.R. §.1.17(e)						
			ii. 🔲	Extension of time fee (37 C.F.R. §§1.136 an	d 1.17)					
	iii. Other									
	b.	b.								
	c. E The Director is hereby authorized to charge any additional fees, or credit any overpayments, to Deposit									
				t No. <u>13-4500</u> Order No. 1232-4785	,	•	,	1		
				SIGNATURE OF APPLICANT, ATTORNI	EY, OR AGE	NT RE	QUIRED			
No-	,, /n	rint/T		nanh D. Dag I.	D N	() 4 - 1 - 1	\ ~~~4\\	54.094		
Name (Print/Type) Joseph D. Eng Jr.					Reg. No.	. (Απу/ <i>F</i>	agent)	54,084		
Signature Joseph D. Ing. W.					Date	July 9.	2004			